

## DHD 50K CRANE BODY

## Minimum 20,000 Lb. G.V.W.R. Medum Duty Chassis

DHD	MODEL			
SPECIFICATIONS	DHD 60	<b>DHD 84</b>	<b>DHD 108</b>	<b>DHD 120</b>
Body Length	107"	131"	155"	167"
Overall Width	98.5"	98.5"	98.5"	98.5"
Front Height	48"	48"	48."	48"
Rear Height	45"	45"	45"	45"
Floor Width	52"	52"	52"	52"
Compartment Depth	22"	22"	22"	22"
Floor to top of Compartment	25"	25"	25"	25"
Front Compartment Length	32"	38"	38"	38"
Second Compartment Length	N/A	18"	24"	28"
Third Compartment Length	N/A	N/A	18"	26"
Horizontal Compartment Length	51"	51"	51"	51"
Rear Compartment Length	24"	24"	24"	24"
Optional Oxy/Ace Compartment Height	60"	60"	60"	60"
Approximate Base Body Weight	2580	3040	3605	3900

Our Promise To You:

" No Compromise"
in Providing the


Very Best Equipment

Available !



DHD 84 CB DRIVER SIDE

\*\* DHD Chassis Requirements: 20,000 Lbs. G.V.W.R. Required Minimum For Body And Chassis Only. Does Not Address Chassis Limitations Imposed By Crane Manufacturer.



**DHD 120 CB** 

For Standard Features and Options See Reverse Side

## STANDARD FEATURES 40K & 50K MODELS

- \* Body Subframe: 6" X 3/16" Crossmembers, 10 Ga Longitudinal Floor Reinforcement 3/16" Torsion Box Subframe for Rigidity
- \* Low Floor Height (Only 6" above Chassis Frame)
- \* Floor: 1/8" Treadplate
- \* Compartment Tops and Rears: 1/8" Treadplate
- \* Crane Compartment: 3/8" H.R. Steel with 1/2" H.R. Top Plate and 4X3X 1/2" angle reinforcement. Completely open for Storage
- \* Major Body Components: 12 Ga. and 10 Ga. H.R.P.O.
- \* Body Designed With Appropriate Material Eliminating Overlays with Rust Pockets
- \* Superior Weather Tight Double Panel Galvaneal Doors
  Automotive Type Replaceable Bulb Rubber Seals
  Over Center Spring Loaded Door Restraints
  Stainless Steel 3 Point Locking T-Handle Latches
  Greaseable XHD Hinges with 5/16" Stainless Steel Pins.

- \* Spring Mounting Kit
- \* 22" Deep Compartments
- \* 12 Gauge Formed Tailgate/ Work Table
- \* Die Formed Ribs in Front Bulk Head
- \* Recessed Cargo Tie Down Rings
- \* All exterior Welds are Continuous Fully Penetrating Welds.

No Caulking is used on these bodies.

- \* HD Shelf Support Channels that hold the shelf where You put it even on the Roughest Road
- \* Anti Rattle Shelf Dividers
- \* A Factory Installed Wiring Loom is Provided with each Body
- \* Stop, Turn, Tail Lights are Sealed Beams
- \* Each Crane Body is Thoroughly Cleaned and Phosphatized Prior to the Application of 2 Mils of PPG Plural Component Epoxy Primer

## OPTIONAL EQUIPMENT ALL MODELS

- \* Drawer Storage Units Mounted on 300 lb.

  Accuride Slides available for any compartment.
- \* A 600 lb. Slide out Mechanics Tool Tray
- \* Material Storage Hooks for storage of Ropes, Cables, Cords, etc. These are available in Fixed, Swivel, and Sliding Swivel arrangements.
- \* 60" Tall Vented Oxygen / Acetylene Storage Compartment available in D - 1 or P - 1. The Compartment comes complete with Reinforced Floor with Bottle Retention Rings, Bottle Tie Downs, Gauge and Torch Holders, and a Hose Rack.
- \* Oxygen / Acetylene compartment with vertical partition and 4 small adjustable shelves

**Authorized Distributor:** 

- \* Additional Adjustable Shelves and Dividers
- \* Egg Crate Fastener Storage Drawer available in either Horizontal Compartment
- \* Theft Deterrent Master Locking System
- \* Cushioned Adjustable Boom Rest (shipped loose)
- \* Hydraulic Crane Prep Package
- \* Compartment Lights
- \* HD Step Bumper
- \* HD Step Bumper with Recessed 2" Ball Plate
- \* HD Step Bumper with Manual Out and Down Outriggers with Spring Retract Legs.
- \* HD Step Bumper with Manual Out and Down
  Outriggers with Spring Retract Legs with Tailshelf
  and Thru Compartment
- \* Hyd. Outrigger/Work Platform/Through Comp.
- \* Header with Work Light Brackets (no lights)

Outriggers Must Be Used On All Models
When Operating Crane !

For the name of your nearest Dutec distributor call 903-868-1917

